

ALS 341/350

ALS[®]

**Flexible, High
Performance
Labelling Head**



400mm O.D for less frequent changeovers



Easy-to-use controls



Accuracy of +/- 0.5mm

The ALS 341/350 labelling heads are reliable, easy to use and accurate to meet the demands of modern production line for high-speeds, zero faults, safety and flexibility.

The ALS 341 and the ALS 350 are controlled by integral electronics giving optimum labelling tolerances, high speed and rapid acceleration to suit the application of a wide range of label size, especially very small labels. Both types may be fitted with either hot stamp, thermal or emboss coders.

The ALS 341 is exceptionally easy to set up with only speed, label photocell and start delay needing to be set before operation.

The ALS 350 is equipped with Automatic Product Speed Following (APSF), web break detection and memory to store up to 16 product/label combinations which can be re-configured easily and quickly at any time.

Both the ALS 341 and the ALS 350 may be readily customised to meet any specific requirements, no matter how specialised. Both types are available as either right or left hand versions to fit easily into any production line.

PAREMA



Verpakkingstechniek

WWW.PAREMA.NL

WORLD CLASS LABELLING SOLUTIONS

ALS 341/350

ALS[®]

SPECIFICATION

Label Width:	10 to 160 mm (including backing paper)
Label Length:	Up to 350 mm (depending on speed and performance)
Label Roll Diameter:	400 mm
Core Diameter:	76 mm (3 in)
Label Rewind:	Collapsible, driver mandrel
Label Stop Accuracy:	+/- 0.5 mm
Control Panel:	ALS 341 - 6 sensitive keys ALS 350 - 4 sensitive keys
Dispensing Speed:	ALS 341 - 0.5 to 50 metres/ minute ALS 350 - Standard: 0.0 to 55 metres/ minute Optional: 0.0 to 80 metres/ minute
Labelling Rate:	600 labels/ minute* *(depending on label size and dispensing speed)
Motor Drives:	Unwinder - Stepper motor Labelling - Stepper motor Rewinder - AC motor
Label Start Delay:	1 - 1000 mm in 0.10 mm steps
Dimensions:	735 x 795 x 400 mm (length x height x width)
Weight:	70 kg
Mains Supply:	110/230 volts, 50Hz
Protection Class:	IP 41
Certification:	CE marked
Sound Level:	76 dB (A)



ABOUT ALS

ALS is a leading European supplier with more than 25 years experience in supplying high quality, competitively priced labelling systems, consumables and accessories.

In addition to the ALS 341/350, the company offers a comprehensive range of label applicators, print & apply systems and thermal transfer printers, to meet labelling requirements across an extensive range of industries and applications.

Advanced Labelling Systems Ltd
Unit B, Bandet Way, Thame
Oxon, OX9 3SJ, United Kingdom
www.als-eu.com

PAREMA

Postbus 2022
NL - 6900 CA Zevenaar
Tel : (+31) 316 33 21 15
Fax : (+31) 316 52 97 37



Verpakkingstechniek

www.parema.nl
info@parema.nl

WORLD CLASS LABELLING SOLUTIONS